NSN 4720-00-370-3329

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-370-3329

Cross Sectional Shape:
Round
Inside Diameter:
0.250 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
Between 0.535 inches and 0.573 inches
Minimum Inside Bending Radius:
1.000 inches
End Connection Design:
Straight 1st end
Connection Type:
Unthreaded external tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and 1st layer braided fabric and outer layer rubber impregnated fabric
Maximum Operating Pressure:
1500.0 pounds per square inch
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and mildew resistant and oil resistant and ozone resistant and vibration resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.500 inches and 14.500 inches
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Specification Data:
81349-mil-h-13444 government specification
Specification Or Standard:
3 type
Shelf Life:
N/a
Unit Of Measure:
onit of Measure.
Demilitarization:
Defininarization:

No

NSN 4720-00-370-3329

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13444 spec.