

View Online at <https://aerobasegroup.com/nsn/4720-00-370-3329>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.535 inches and 0.573 inches

**Minimum Inside Bending Radius:**

1.000 inches

**End Connection Design:**

Straight 1st end

**Connection Type:**

Unthreaded external tube 1st end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided wire and 1st layer braided fabric and outer layer rubber impregnated fabric

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and mildew resistant and oil resistant and ozone resistant and vibration resistant

**Vacuum In Torr:**

254.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

13.500 inches and 14.500 inches

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Specification Data:**

81349-mil-h-13444 government specification

**Specification Or Standard:**

3 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13444 spec.