NSN 4720-00-370-9487

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-370-9487

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.410 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.560 inches
Minimum Inside Bending Radius:
4.600 inches
Exterior Color:
Natural
Quick Disconnect Size:
0.625 inches 2nd end
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and nuts drilled for lockwire and reusable end fittings
Burst Test Pressure:
1950.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
650.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
1300.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:

Corrosion resistant

NSN 4720-00-370-9487

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
27.790 inches working
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A542a0