NSN 4720-00-373-1024

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-373-1024

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
158.0 degrees fahrenheit single response
Outside Diameter:
0.970 inches
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
Outer layer spirally wrapped polyamide fabric and 1st layer rubber impregnated cotton fabric
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Light resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
60.000 inches
Special Markings:
Water
Media For Which Designed:
Water, fresh single response
Thread Series Designator:
Nh 2nd end
Specification Data:

opcomodion bata

81348-zz-h-601 government specification

NSN 4720-00-373-1024

Nonmetallic Hose Assembly - Page 2 of 2



Sp	ecific	ation	Or S	Stand	lard:
----	--------	-------	------	-------	-------

1 grade and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0