NSN 4720-00-374-1725



Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-374-1725

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches

0.750 inches

Minimum Inside Bending Radius:

1.750 inches

Connection Style:

Swivel, plain 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 2nd end

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

2nd layer braided textile yarn and 1st layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

225.0 pounds per square inch

Thread Size:

0.250 inches 2nd end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.000 inches

Media For Which Designed:

Air single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

NSN 4720-00-374-1725

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0