## NSN 4720-00-374-2211

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-374-2211

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end  Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
Harnischfeger truck fork lift model omega t-650
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
2nd layer rubber impregnated cotton fabric and 1st layer rubber impregnated cotton fabric and outer layer molded rubber, synthetic
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
42.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.000 inches and 10.250 inches
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:

Unf 1st end

## NSN 4720-00-374-2211

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0