

View Online at <https://aerobasegroup.com/nsn/4720-00-374-2222>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

24 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

2nd layer rubber impregnated braided cotton cord and 1st layer rubber impregnated braided cotton cord and outer layer molded rubber, synthetic

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.281 inches and 15.531 inches

Special Features:

1st end connection thd pitch is 0.4104 in. Min. 0.4144 in. Max, 2nd end connection thd pitch diameter is 0.4014 @in. Min. 0.4050 in. Max

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0