NSN 4720-00-374-9247

Cross Sectional Shape:

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-374-9247

| Round |
|---|
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.719 inches |
| Connection Style: |
| Swivel nut, compression 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 20 1st end |
| Burst Test Pressure: |
| 850.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber, synthetic and 1st layer rubber impregnated cotton fabric |
| Thread Size: |
| 0.750 inches 1st end |
| Hydrostatic Test Pressure: |
| 524.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Fuel resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 9.375 inches and 9.625 inches |
| Seat Radius: |
| 0.1955 inches 1st end |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unef 1st end |
| Shalf Life: |

NSN 4720-00-374-9247

Nonmetallic Hose Assembly - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0