Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-375-7031

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and	200.0 degrees fahrenheit single response
Outside Diameter:	
0.625 inches	
Minimum Inside Bending Rad	dius:
3.000 inches	
Connection Style:	
Plain 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	t
Burst Test Pressure:	
1200.0 pounds per square inch	1
Layer Composition And Loca	ation:
2nd layer braided rayon cord a	nd 1st layer braided rayon cord and outer layer molded rubber, chloroprene
Maximum Operating Pressur	e:
300.0 pounds per square inch	
Thread Size:	
0.250 inches 1st end	
Outer Covering Environment	al Protection:
Cold resistant and oil resistant	and waterproof
Inside Surface Condition:	
Smooth	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A542a0	