

View Online at <https://aerobasegroup.com/nsn/4720-00-375-7151>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.969 inches and 1.031 inches

Outside Diameter:

Between 1.078 inches and 1.140 inches

Hose Or Tubing Specification/std Data:

Fed zz-h-611, grade b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Fed ww-c-00624, type a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal hose 1st end

Thready Qty Per Inch (tpi):

11-1/2 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

500.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer molded rubber

Thread Size:

1.000 inches 1st end

Hydrostatic Test Pressure:

150.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

144.000 inches

Special Features:

Media For Which Designed:

Water, fresh single response

Thread Series Designator:

Npsh 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0