Metallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-375-8641

Cross Sectional Shape:         Round         Inside Diameter:         0.750 inches         Outside Diameter:         0.875 inches         Minimun Inside Bending Radius:         7.500 inches         Inner Conveying Tube Style:         Annular close-pitch corrugated         End Connection Design:         Straight 1st end         Connection Type:         Unthreaded external tube 1st end         Features Provided:         Identical ends         Layer Composition And Location:         Outer layer braided bronze wire         Hydrostatic Test Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Messuring Method And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         Na         Unit Of Measure:            Demilitarization:         No         Fig:	
Anside Diameter:         0.750 inches         Dutside Diameter:         0.875 inches         Minimum Inside Bending Radius:         7.500 inches         Inner Conveying Tube Style:         Annular close-pitch corrugated         End Connection Design:         Straight 1st end         Connection Type:         Unthreaded external tube 1st end         Features Provided:         Identical ends         Layer Composition And Location:         Outer layer braided bronze wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Measuring Method And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Sheft Iffe:         Na         Unit Of Measure:         -         Demilitarization:         Na         Dirition:         Na         Dirition:         It of Measure:         It o	Cross Sectional Shape:
0.750 inches         0.875 inches         Minimun Inside Bending Radius:         7.500 inches         Inner Conveying Tube Style:         Annular close-pitch corrugated         End Connection Design:         Straight 1st end         Connection Type:         Unthreaded external tube 1st end         Features Provided:         Identical ends         Contest pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Mesuring Method And Length:         15.75 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         Na         Unit of Measure:         Io         Ist 1st 1st 1st 1st 1st 1st 1st 1st 1st 1	Round
Outside Diameter:0.875 inchesMinimun Inside Bending Radius:7.500 inchesInner Conveying Tube Style:Annular close-pitch corrugatedEnd Connection Design:Straight 1st endConnection Type:Unthreaded external tube 1st endFeatures Provided:Identical endsLayer Composition And Location:Outer layer braided bronze wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:2500.0 pounds per square inchMesuring Method And Length:15.750 inchesOutside Diameter Tube Accommodated:0.875 inches 1st endShelf Life:NaUnit of Measure:Init of Measure:Init of Measure:Image:Image:NaFig:	Inside Diameter:
0.875 inches  innum Inside Bending Radius:  7.500 inches  Inner Conveying Tube Style: Annular close-pitch corrugated  End Connection Design: Straight 1st end  Connection Type: Unthreaded external tube 1st end  Features Provided: Identical ends  Layer Composition And Location: Outer layer braided bronze wire  Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 2500.0 pounds per square inch Maximus Operating Nessure: 15.750 inches  Outside Diameter Tube Accommodated: 0.875 inches 1st end  Nature Inter Int	0.750 inches
Minimum Inside Bending Radius:         7.500 inches         Inner Conveying Tube Style:         Annular close-pitch corrugated         End Connection Design:         Straight 1st end         Connection Type:         Unthreaded external tube 1st end         Features Provided:         Identical ends         Layer Composition And Location:         Outer layer braided bronze wire         Maximum Operating Pressure:         1500.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Measuring Method And Length:         15.750 inches         Outside Dlameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         Iva         Iva         Fer         Fig:	Outside Diameter:
7.500 inches Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 1st end Connection Type: Unthreaded external tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 2500.0 pounds per square inch Measuring Method And Length: 15.750 inches Stel Life: Na Identical end Identical ends Id	0.875 inches
Inner Conveying Tube Style:         Annular close-pitch corrugated         End Connection Design:         Straight 1st end         Connection Type:         Unthreaded external tube 1st end         Features Provided:         Identical ends         Layer Composition And Location:         Outer layer braided bronze wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Measuring Method And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         Iva         Init of Measure:         -         Pomilitarization:         No         Fig:	Minimum Inside Bending Radius:
Annular close-pitch corrugated End Connection Design: Straight 1st end Connection Type: Unthreaded external tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 150.0 pounds per square inch Measuring Method And Length: 15.750 inches Dutside Diameter Tube Accommodated: 0.875 inches 1st end Kal Diameter Tube Accommodated: Na Diameter Tube Accommodated: Control Contert Strain St	7.500 inches
End Connection Design:         Straight 1st end         Connection Type:         Unthreaded external tube 1st end         Features Provided:         Identical ends         Layer Composition And Location:         Outer layer braided bronze wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Measuring Method And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	Inner Conveying Tube Style:
Straight 1st end Connection Type: Unthreaded external tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 2500.0 pounds per square inch Measuring Method And Length: 15.750 inches Outside Diameter Tube Accommodated: 0.875 inches 1st end Sheff Life: N/a Uit Of Measure: - - Demilitarization: No	Annular close-pitch corrugated
Connection Type:         Unthreaded external tube 1st end         Features Provided:         Identical ends         Layer Composition And Location:         Outer layer braided bronze wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Measuring Method And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         N/a         Dint of Measure:         -         -         Penilitarization:         No         Fig:	End Connection Design:
Unthreaded external tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 2500.0 pounds per square inch Measuring Method And Length: 15.750 inches Outside Diameter Tube Accommodated: 0.875 inches 1st end Shelf Life: N/a Unit Of Measure: 	Straight 1st end
Features Provided:         Identical ends         Layer Composition And Location:         Outer layer braided bronze wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Maximum Querating Nethod And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         N/a         Unit Of Measure:            Penilitarization:         No         Fig:	Connection Type:
Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 2500.0 pounds per square inch Measuring Method And Length: 15.750 inches Outside Diameter Tube Accommodated: 0.875 inches 1st end Shelf Life: N/a Unit Of Measure: Pemilitarization: No	Unthreaded external tube 1st end
Layer Composition And Location:         Outer layer braided bronze wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Measuring Method And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         N/a         Unit Of Measure:            Pomilitarization:         No         Fig:	Features Provided:
Outer layer braided bronze wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         2500.0 pounds per square inch         Measuring Method And Length:         15.750 inches         Outside Diameter Tube Accommodated:         0.875 inches 1st end         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Identical ends
Maximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:2500.0 pounds per square inchMeasuring Method And Length:15.750 inchesOutside Diameter Tube Accommodated:0.875 inches 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Layer Composition And Location:
150.0 pounds per square inch Hydrostatic Test Pressure: 2500.0 pounds per square inch Measuring Method And Length: 15.750 inches Outside Diameter Tube Accommodated: 0.875 inches 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Outer layer braided bronze wire
Hydrostatic Test Pressure:2500.0 pounds per square inchMeasuring Method And Length:15.750 inches0tside Diameter Tube Accommodated:0.875 inches 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Maximum Operating Pressure:
2500.0 pounds per square inch Measuring Method And Length: 15.750 inches Outside Diameter Tube Accommodated: 0.875 inches 1st end 0.875 inches 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	150.0 pounds per square inch
Measuring Method And Length:15.750 inchesOutside Diameter Tube Accommodated:0.875 inches 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Hydrostatic Test Pressure:
15.750 inches Outside Diameter Tube Accommodated: 0.875 inches 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No	2500.0 pounds per square inch
Outside Diameter Tube Accommodated:0.875 inches 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Measuring Method And Length:
0.875 inches 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	15.750 inches
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Outside Diameter Tube Accommodated:
N/a Unit Of Measure:  Demilitarization: No Fiig:	0.875 inches 1st end
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
	Fiig:
A542a0	A542a0