NSN 4720-00-376-1774

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-376-1774

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.781 inches
Minimum Inside Bending Radius:
4.000 inches
Quick Disconnect Size:
1.010 inches 2nd end
Connection Style:
Push (internal) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided fiber
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.5000 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and grease resistant and oil resistant and ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
74.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Npt 1st end

NSN 4720-00-376-1774

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0