Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-376-1777

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.750 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
1600.0 pounds per square inch	
Layer Composition And Location:	
Outer layer molded rubber, synthetic and 1st layer braided textile yarn	
Maximum Operating Pressure:	
400.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
45.0 degrees 1st end	
Hydrostatic Test Pressure:	
800.0 pounds per square inch	
Outer Covering Environmental Protection:	
Oil resistant and weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
24.250 inches	
Media For Which Designed:	
Hydraulic fluid single response	

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

