Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-376-8306

Cross Section	al Shape:
Round	
Thread Class:	
2b 1st end	
Thread Directi	ion:
Right-hand 1st	end
Inside Diamete	er:
Between 0.183	inches and 0.204 inches
Tempurature F	Rating:
-40.0 degrees f	ahrenheit and 275.0 degrees fahrenheit single response
Outside Diame	eter:
Between 0.492	inches and 0.540 inches
Connection St	yle:
Swivel nut flare	a 1st end
End Connection	on Design:
Straight 1st end	t de la constante de
Connection Ty	/pe:
Threaded interr	nal tube 1st end
Burst Test Pre	essure:
12000.0 pound	s per square inch
Layer Compos	sition And Location:
2nd layer braid	ed steel wire and 1st layer braided cotton cord and outer layer rubber impregnated cotton fabric
Maximum Ope	erating Pressure:
3000.0 pounds	per square inch
Thread Size:	
0.438 inches 1	st end
Seat Angle:	
45.0 degrees 1	st end
Inside Surface	e Condition:
Smooth	
Measuring Me	thod And Length:
29.000 inches	excluding end fittings
Media For Whi	ich Designed:
Fuel/oil, hydrod	carbon single response
Thread Series	Designator:
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	on:
No	

## NSN 4720-00-376-8306

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

