NSN 4720-00-376-8456

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-376-8456 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.375 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 27 2nd end **Burst Test Pressure:** 1200.0 pounds per square inch **Layer Composition And Location:** 2nd layer spirally laid steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 300.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 45.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 5.250 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life:

--

N/a

Unit Of Measure:

NSN 4720-00-376-8456

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0