Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-378-8452

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -15.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.920 inches |
| Minimum Inside Bending Radius: |
| 5.500 inches |
| Exterior Color: |
| Red |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Thready Qty Per Inch (tpi): |
| 14 1st end |
| Burst Test Pressure: |
| 2500.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided textile yarn and 1st layer braided wire |
| Maximum Operating Pressure: |
| 350.0 pounds per square inch |
| Thread Size: |
| 0.875 inches 1st end |
| Seat Angle: |
| 45.0 degrees 1st end |
| Vacuum In Torr: |
| 28.0 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 96.000 inches |

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0