NSN 4720-00-381-5439



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-381-5439 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.875 inches **Minimum Inside Bending Radius:** 6.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 7000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and 1st layer braided textile yarn and outer layer braided textile yarn **Maximum Operating Pressure:** 1750.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3500.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and fuel resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 30.000 inches

Air and gas single response **Thread Series Designator:**

Media For Which Designed:

Unf 1st end

NSN 4720-00-381-5439

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0