Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-382-7889

····· · ······························
Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
6.000 inches
Connection Style:
Gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external hose 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
Outer layer woven cotton with interwoven steel wire and 1st layer molded rubber, synthetic
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
1.750 inches 1st end
Outer Covering Environmental Protection:
Fuel resistant
Vacuum In Torr:
127.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
33.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0