Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-383-5718

Cross Sectional Sha	ipe:
Round	
-	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.344 inches	
Tempurature Rating	
	heit and 300.0 degrees fahrenheit single response
Outside Diameter:	
0.547 inches	
Minimum Inside Ber	nding Radius:
2.500 inches	
Connection Style:	
Swivel nut flare 1st e	nd
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tub	e 1st end
Burst Test Pressure	: :
6000.0 pounds per so	quare inch
Layer Composition	And Location:
Outer layer braided c	orrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage
Maximum Operating	Pressure:
1000.0 pounds per so	quare inch
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pro	essure:
3000.0 pounds per so	quare inch
Inside Surface Cond	lition:
Smooth	
Measuring Method	And Length:
10.250 inches workir	ng
Media For Which De	signed:
Fuel/oil, hydrocarbor	a single response
Thread Series Desig	inator:
Unjf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0