Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-384-0494

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.578 inches	
Connection Style:	
Plain optional end 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal pipe 1st end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.250 inches 2nd end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Fuel resistant and mildew resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
72.000 inches working	
Special Features:	
W/1 adapter and 1 regulating valve	
Media For Which Designed:	
Hydraulic fluid single response	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 4720-00-384-0494

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0