

View Online at <https://aerobasegroup.com/nsn/4720-00-390-5445>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

400.0 degrees fahrenheit single response

Outside Diameter:

1.031 inches

Connection Style:

Plain optional end 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal pipe 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

2nd layer polytetrafluoroethylene impregnated glass fiber and 1st layer polytetrafluoroethylene impregnated glass fiber and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

140.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Heat resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches excluding end fittings

Special Features:

Heating element attached to each coupling 0.062 in. Diameter cable 7 by 7 construction, cres steel wire, a return cable, mil-c-915, 50 ft lg @taped to hose assembly, assembly used for hot plastic paint spraying

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0