

View Online at <https://aerobasegroup.com/nsn/4720-00-390-5445>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Tempurature Rating:**

400.0 degrees fahrenheit single response

**Outside Diameter:**

1.031 inches

**Connection Style:**

Plain optional end 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal pipe 1st end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer polytetrafluoroethylene impregnated glass fiber and 1st layer polytetrafluoroethylene impregnated glass fiber and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

140.0 pounds per square inch

**Thread Size:**

0.375 inches 1st end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Heat resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches excluding end fittings

**Special Features:**

Heating element attached to each coupling 0.062 in. Diameter cable 7 by 7 construction, cres steel wire, a return cable, mil-c-915, 50 ft lg @taped to hose assembly, assembly used for hot plastic paint spraying

**Thread Series Designator:**

Npt 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0