NSN 4720-00-393-2040

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-393-2040

20 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.507 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.870 inches					
Minimum Inside Bending Radius:					
3.000 inches					
Exterior Color:					
Natural					
Angle Between Rigid Elbow Fittings In Deg:					
45.0					
Connection Style:					
Swivel nut with compression sleeve 2nd end					
End Connection Design:					
Elbow 2nd end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
10000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer molded polyurethane					
Maximum Operating Pressure:					
1500.0 pounds per square inch					
Thread Size:					
0.750 inches 2nd end					
Seat Angle:					
37.0 degrees 2nd end					
Hydrostatic Test Pressure:					
3000.0 pounds per square inch					
Flow Angle:					
90.0 degrees 2nd end					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
22.380 inches excluding end fittings					

NSN 4720-00-393-2040

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Hydraulic fluid single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0