

View Online at <https://aerobasegroup.com/nsn/4720-00-393-9841>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.516 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

2nd layer rubber impregnated braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Vacuum In Torr:

28.5

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.000 inches

Special Features:

Furnished with a clear plastic tube 0.578 in. Od x 11.000 in. Lg and a prebent aluminum tube 0.625 in. Od x 5.500 in. Lg

Media For Which Designed:

Air and alcohol, ethyl and hydraulic fluid and fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0