Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-394-3306

Cro	oss Sectional Shape:
Ro	und
Th	read Direction:
Rig	pht-hand 1st end
Ins	side Diameter:
0.5	00 inches
Те	mpurature Rating:
-40	0.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Ou	tside Diameter:
0.9	69 inches
Miı	nimum Inside Bending Radius:
7.0	00 inches
Ex	terior Color:
Bla	ick
Co	nnection Style:
Pla	in 1st end
En	d Connection Design:
Str	aight 1st end
Co	nnection Type:
Th	readed external pipe 1st end
Bu	rst Test Pressure:
14(000.0 pounds per square inch
Lay	yer Composition And Location:
2no	d layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, synthetic
Ма	ximum Operating Pressure:
350	00.0 pounds per square inch
Th	read Size:
0.5	00 inches 1st end
Hy	drostatic Test Pressure:
700	00.0 pounds per square inch
Ou	ter Covering Environmental Protection:
Oil	resistant and weatherproof
Ins	ide Surface Condition:
Sm	nooth
Me	asuring Method And Length:
13.	250 inches
Me	dia For Which Designed:
Fu	el/oil, hydrocarbon single response
Th	read Series Designator:
Np	tf 1st end
Sh	elf Life:
N/a	a de la constante de

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0