NSN 4720-00-395-6692

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-395-6692

| Thread Class: |
|---|
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.625 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 1000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 300.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant and fuel resistant and oil resistant |
| Vacuum In Torr: |
| 254.0 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 4.875 inches working |
| Media For Which Designed: |
| Air single response |

NSN 4720-00-395-6692

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Designator: |
|--------|---------------|--------------------|
| | | |

Unjf 1st end

Specification Data:

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0