

View Online at <https://aerobasegroup.com/nsn/4720-00-400-2838>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.380 inches and 0.390 inches 2nd end

**Outside Diameter:**

2.000 inches

**Minimum Inside Bending Radius:**

18.000 inches

**Flange Outside Diameter:**

2.000 inches 2nd end

**Connection Style:**

Swivel nut flare 1st end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel 2nd end

**Fitting Component And Surface Treatment:**

Complete fitting anodize 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

12 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

12000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer spirally wrapped steel fabric

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

1.625 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Flow Angle:**

45.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

29.625 inches

**Second End Swivel Action Capability:**

Not included

**Flange Style:**

Round w/ out bolt holes 2nd end

**Special Features:**

Inner conveying tube material-rubber, chloroprene

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0