## NSN 4720-00-400-3150

1000.0 pounds per square inch

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-400-3150

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Hose Or Tubing Specification/std Data:
Aeroquip 601-4 standard (includes industry or association standards, individual manufactureer standards, etc.).
First End Fitting Specification/std Data:
Aeroquip 816-4 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Socket aluminum alloy 2nd end
Fitting Component And Surface Treatment:
Nut cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Second End Relationship With First End:
Identical
Burst Test Pressure:
6000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:

## **NSN 4720-00-400-3150**Nonmetallic Hose Assembly - Page 2 of 2



Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
144.000 inches working
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0