Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-400-6757

Cr	oss Sectional Shape:
Ro	bund
Th	aread Class:
2b	1st end
Th	read Direction:
Ri	ght-hand 1st end
Ins	side Diameter:
0.8	380 inches
Те	empurature Rating:
-4(0.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Οι	utside Diameter:
1.2	230 inches
Mi	nimum Inside Bending Radius:
7.3	380 inches
Co	onnection Style:
S٧	vivel nut flare 1st end
En	nd Connection Design:
Str	raight 2nd end
Co	onnection Type:
Th	readed internal tube 1st end
Fe	atures Provided:
Re	eusable end fittings
Th	ready Qty Per Inch (tpi):
12	1st end
Βu	urst Test Pressure:
32	00.0 pounds per square inch
La	yer Composition And Location:
2n	d layer braided wire and 1st layer braided textile yarn and outer layer rubber impregnated braided cotton cord
Ma	aximum Operating Pressure:
80	0.0 pounds per square inch
Th	iread Size:
1.0	000 inches 2nd end
Se	eat Angle:
37	.0 degrees 1st end
Ins	side Surface Condition:
Sn	nooth
Me	easuring Method And Length:
87	.000 inches
Me	edia For Which Designed:
Air	and fuel/oil, hydrocarbon single response
Th	read Series Designator:
	1 1st end

NSN 4720-00-400-6757

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

