NSN 4720-00-402-5123

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-402-5123

Cross Sectional Snape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.321 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Bolt Circle Diameter:
1.985 inches 2nd end
Flange Thickness:
0.446 inches 2nd end
Outside Diameter:
0.456 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Natural
Bolt Hole Quantity:
2 2nd end
Flange Length:
2.922 inches 2nd end
Flange Width:
1.390 inches 2nd end
Connection Style:
Raised swivel 2nd end
Bolt Hole Diameter:
0.500 inches 2nd end
Raised Face Height:
0.184 inches 2nd end
Raised Face Diameter:
1.000 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 1st end

8000.0 pounds per square inch

Burst Test Pressure:

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

NSN 4720-00-402-5123

Nonmetallic Hose Assembly - Page 2 of 2



Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.000 inches
Flange Style:
Oval 2nd end
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0