NSN 4720-00-402-5176

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-402-5176
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
Between 0.578 inches and 0.625 inches
Minimum Inside Bending Radius:
4.000 inches
Hose Or Tubing Specification/std Data:
Mil mil-h-5593, size 6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
First End Fitting Specification/std Data:
Mil ms27404-6 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting aluminum alloy all ends
Fitting Component And Surface Treatment:
Complete fitting anodize 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Second End Relationship With First End:
Identical
Burst Test Pressure:
1000.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer molded rubber

Thread Size: 0.562 inches 1st end

Maximum Operating Pressure: 150.0 pounds per square inch

NSN 4720-00-402-5176

Nonmetallic Hose Assembly - Page 2 of 2

