Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-403-9973

-	
	ional Shape:
Round	
Thread Clas	SS:
3b 1st end	
Thread Dire	
Right-hand '	1st end
Inside Diam	neter:
0.406 inches	S
Tempuratu	re Rating:
-67.0 degree	es fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Dia	ameter:
Between 0.5	546 inches and 0.585 inches
Minimum In	nside Bending Radius:
4.625 inches	S
Connection	a Style:
Swivel nut fl	are 2nd end
End Conne	ction Design:
Straight 1st	end
Connection	а Туре:
Threaded in	ternal tube 1st end
Burst Test	Pressure:
6000.0 pour	nds per square inch
Layer Com	position And Location:
Outer layer	braided corrosion resistant steel wire
Maximum C	Operating Pressure:
1500.0 pour	nds per square inch
Thread Size	e:
0.750 inches	s 2nd end
Seat Angle:	
37.0 degree	s 2nd end
Hydrostatic	: Test Pressure:
3000.0 pour	nds per square inch
Flow Angle	:
45.0 degree	s 2nd end
Inside Surfa	ace Condition:
Smooth	
Measuring	Method And Length:
7.500 inches	
	ies Designator:
Unjf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0