

View Online at <https://aerobasegroup.com/nsn/4720-00-405-5144>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.218 inches

Outside Diameter:

0.468 inches

Minimum Inside Bending Radius:

2.000 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.500 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0