Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-406-3304

Cross S	Sectional Shape:
Round	
Thread	Class:
2b 1st e	nd
Thread	Direction:
Right-ha	and 1st end
Inside I	Diameter:
0.900 ir	ches
Tempu	ature Rating:
-40.0 de	grees fahrenheit and 275.0 degrees fahrenheit single response
Outside	Diameter:
1.235 ir	ches
Minimu	m Inside Bending Radius:
7.380 ir	ches
Exterio	r Color:
Black	
Connec	tion Style:
Swivel r	ut flare 1st end
End Co	nnection Design:
Straight	2nd end
Connec	tion Type:
Threade	ed internal tube 1st end
Thread	/ Qty Per Inch (tpi):
14 1st e	nd
Burst T	est Pressure:
3200.0	bounds per square inch
Layer C	omposition And Location:
2nd lay	er braided steel wire and 1st layer braided fiber and outer layer rubber impregnated braided cotton cord
Maximu	m Operating Pressure:
800.0 p	bunds per square inch
Thread	Size:
0.750 ir	ches 2nd end
Seat Ar	gle:
37.0 de	grees 1st end
Hydros	tatic Test Pressure:
1600.0	bounds per square inch
Inside	Surface Condition:
Smooth	
Measur	ing Method And Length:
16.750	nches
Media I	or Which Designed:
E	hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0