NSN 4720-00-406-3498 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-406-3498 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response **Outside Diameter:** 0.790 inches **Minimum Inside Bending Radius: 7.750** inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

1.000 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches

NSN 4720-00-406-3498

Nonmetallic Hose Assembly - Page 2 of 2



Ihread	Series	Designator
Unf 1st	end	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0