Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-407-0661

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	}
Outside Diameter:	
Between 0.594 inches and 0.656 inches	
Connection Style:	
Swivel nut, gasket seal 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal pipe 1st end	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided cotton cord and outer layer molded rubber, chloropre	ne
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
0.250 inches 2nd end	
Hydrostatic Test Pressure:	
500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Fuel resistant and mildew resistant and oil resistant and ozone resistant	(
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
17.875 inches and 18.125 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Npt 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-00-407-0661

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

