

View Online at <https://aerobasegroup.com/nsn/4720-00-407-8420>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.562 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.703 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings and self-sealing

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

2nd layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.500 inches working

Special Features:

Sleeve, bullet sealing rubber covered with a rubber impregnated fiber wrap and two cres clamps

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0