Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-409-0770

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.672 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and 1st layer braided cotton cord and outer layer molded rubber
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
45.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

26.750 inches

Media For Which Designed:

Air and fuel/oil, hydrocarbon and water, fresh single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0