

View Online at <https://aerobasegroup.com/nsn/4720-00-409-0775>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.212 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

0.507 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Natural

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.625 inches working

Special Features:

External protection type and location- chafe guard, polyvinyl chloride acetate , inner conveying tube material-plastic, polytetrafluoroethylene; permanently attached end fittings

Thread Series Designator:

Unf 1st end

Specification Data:

Mil mil-h-38360, size 4 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0