Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-409-6160

(Cross Sectional Shape:
I	Round
•	Thread Direction:
I	Right-hand 1st end
I	Inside Diameter:
(0.250 inches
-	Tempurature Rating:
	40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
(Outside Diameter:
(0.600 inches
I	Minimum Inside Bending Radius:
;	3.000 inches
I	Exterior Color:
I	Black
(Connection Style:
:	Swivel, plain 2nd end
I	End Connection Design:
:	Straight 2nd end
(Connection Type:
-	Threaded external pipe 2nd end
I	Burst Test Pressure:
9	900.0 pounds per square inch
I	Layer Composition And Location:
2	2nd layer braided synthetic cord and 1st layer braided synthetic cord and outer layer molded rubber, chloroprene
I	Maximum Operating Pressure:
2	225.0 pounds per square inch
•	Thread Size:
	0.125 inches 2nd end
I	Hydrostatic Test Pressure:
	450.0 pounds per square inch
	Outer Covering Environmental Protection:
(Oil resistant
I	Inside Surface Condition:
	Smooth
	Measuring Method And Length:
	14.125 inches
•	Thread Series Designator:
	Npt 1st end
	Shelf Life:
	N/a
l	Unit Of Measure:
	-

NSN 4720-00-409-6160

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

