Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-410-1185

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.750 inches	
Outside Diameter:	
1.086 inches	
Minimum Inside Bending Radius:	
9.500 inches	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
18 2nd end	
Burst Test Pressure:	
5000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer molded rubber, chloroprene and 1st layer braided steel wire	
Maximum Operating Pressure:	
1250.0 pounds per square inch	
Thread Size:	
1.062 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	
2500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Ozone resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
39.750 inches	
Media For Which Designed:	
Hydraulic fluid single response	
Thread Series Designator:	
Un 1st end	

NSN 4720-00-410-1185

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

