

NSN 4720-00-410-6287 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-410-6287 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.219 inches **Minimum Inside Bending Radius:** 9.500 inches **Connection Style:** Plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 5000.0 pounds per square inch

**Layer Composition And Location:** 

Outer layer molded rubber, synthetic and 1st layer braided wire

**Maximum Operating Pressure:** 

1250.0 pounds per square inch

**Thread Size:** 

0.750 inches 1st end

**Hydrostatic Test Pressure:** 

2500.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Oil resistant and weatherproof

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

182.000 inches

Media For Which Designed:

Hydraulic fluid single response

**Thread Series Designator:** 

Npt 1st end

Shelf Life:

N/a

## NSN 4720-00-410-6287

Nonmetallic Hose Assembly - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A542a0