

View Online at <https://aerobasegroup.com/nsn/4720-00-411-5617>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b and 2a 2nd end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.190 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.485 inches

**Minimum Inside Bending Radius:**

1.500 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting dichromate 1st end

**Connection Type:**

Threaded internal and external tube 2nd end

**Thready Qty Per Inch (tpi):**

24 2nd end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

4000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

0.438 inches and 0.625 inches 2nd end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

2000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

20.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Uns and unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0