## NSN 4720-00-412-7587

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-412-7587

0.391 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.593 inches
Minimum Inside Bending Radius:
4.625 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
70.000 inches working
Special Features:
Fittings permanently attached at factory

## NSN 4720-00-412-7587

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0