Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-413-3406

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.406 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
Between 0.714 inches and 0.760 inches	
Minimum Inside Bending Radius:	
1.750 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
4000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and 1st layer braided cotton cord and outer layer rubber impr	regnated braided cotton cord
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
45.0 degrees 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
47.000 inches	
Media For Which Designed:	
Air single response	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 4720-00-413-3406

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

