## NSN 4720-00-413-3504

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-413-3504

Inside Diameter:
0.212 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.390 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
5000.0 pourids per square mon
Outer Covering Environmental Protection:
Outer Covering Environmental Protection:
Outer Covering Environmental Protection:  Corrosion resistant
Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:
Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:  Smooth
Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:

## NSN 4720-00-413-3504

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

81343-as115 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0