NSN 4720-00-417-2341

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-417-2341

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.750 inches
Minimum Inside Bending Radius:
11.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
2nd layer rubber impregnated braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
1.875 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant
Vacuum In Torr:

50.8

NSN 4720-00-417-2341

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
65.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0