Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-418-4880

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.500 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.810 inches  |
| Minimum Inside Bending Radius:  |
| 7.000 inches  |
| Connection Style:   |
| Swivel nut flare 2nd end  |
| End Connection Design:  |
| Straight 2nd end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 8000.0 pounds per square inch   |
| Layer Composition And Location:                                       |
| Outer layer molded rubber, synthetic and 1st layer braided steel wire |
| Maximum Operating Pressure:   |
| 2000.0 pounds per square inch   |
| Thread Size:  |
| 0.875 inches 1st end  |
| Seat Angle:   |
| 45.0 degrees 2nd end  |
| Hydrostatic Test Pressure:  |
| 4000.0 pounds per square inch   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 31.625 inches   |
| Thread Series Designator:   |
| Unf 2nd end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 4720-00-418-4880

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

