

View Online at <https://aerobasegroup.com/nsn/4720-00-418-4883>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded external tube 1st end

**Burst Test Pressure:**

4500.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided fabric and 1st layer braided fabric and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1125.0 pounds per square inch

**Thread Size:**

0.625 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2250.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

25.500 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0