NSN 4720-00-419-0479

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-419-0479

| Cross Sectional Shape: Round Inside Diameter: 2.000 inches first end Minimum Inside Bending Radius: 1.000 inches Endlength: 1.500 inches first end Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: 81349-mil-h-8796 government specification |
|---|
| Inside Diameter: 2.000 inches first end Minimum Inside Bending Radius: 1.000 inches Endlength: 1.500 inches first end Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| 2.000 inches first end Minimum Inside Bending Radius: 1.000 inches Endlength: 1.500 inches first end Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Minimum Inside Bending Radius: 1.000 inches Endlength: 1.500 inches first end Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Endlength: 1.500 inches first end Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Endlength: 1.500 inches first end Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| 1.500 inches first end Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Connection Style: Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Round first end Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Connection Type: Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Soft first end End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| End Inside Diameter: 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| 2.000 inches first end Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Maximum Operating Pressure: 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| 16.0 pounds per square inch Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Measuring Method And Length: 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| 11.500 inches Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Material Specification: Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply Style Designator: Helically wound continous wire supported Specification Data: |
| Style Designator: Helically wound continous wire supported Specification Data: |
| Helically wound continous wire supported Specification Data: |
| Specification Data: |
| • |
| 81349-mil-h-8796 government specification |
| |
| Specification Or Standard: |
| 2 type and 2 class |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A229a0 |
| Mil-std (military Standard): |
| Mil-h-8796 spec. |
| |